

EMC VNX SERIES UNIFIED STORAGE SYSTEMS

EMC® VNX™ series unified storage systems deliver uncompromising scalability and flexibility for the mid-tier while providing market-leading simplicity and efficiency to minimize total cost of ownership.



Specifications

ARCHITECTURE

Based on the powerful new family of Intel Xeon-5600 processors, the EMC VNX implements a modular architecture that integrates hardware components for block, file, and object with concurrent support for native NAS, iSCSI, Fibre Channel, and FCoE protocols. The series delivers file (NAS) functionality via two-to-eight X-blade data movers and block (iSCSI, FCoE, and FC) storage via dual storage processors leveraging full 6 Gb SAS disk drive topology. The unified configuration includes the following rack-mounted enclosures:

- Disk processor enclosure (holds disk drives) or storage processor enclosure (requires disk drive tray) plus standby power system to deliver block protocols
- One or more data mover enclosures to deliver file protocols (optional)
- Control station (optional)



VNX PHYSICAL SPECIFICATIONS

BLOCK COMPONENTS	VNX5100	VNX5300	VNX5500	VNX5700	VNX7500
Min/Max Drives	4/75	4/125	4/250	4/500	4/1000
Array Enclosure	3U Disk Processor Enclosure (Holds 15x3.5" or 25x2.5" SAS/Flash drives)	3U Disk Processor Enclosure (Holds 15x3.5" or 25x2.5" SAS/Flash drives)	3U Disk Processor Enclosure (Holds 15x3.5" or 25x2.5" SAS/Flash drives)	2U Storage Processor Enclosure (No drives)	2U Storage Processor Enclosure (No drives)
Drive Enclosure Options (DAE)	25 x 2.5" SAS/Flash drives – 2 U 15 x 3.5" SAS/Flash drives – 3 U	25 x 2.5" SAS/Flash drives – 2 U 15 x 3.5" SAS/Flash drives – 3 U	25 x 2.5" SAS/Flash drives – 2 U 15 x 3.5" SAS/Flash drives – 3 U	25 x 2.5" SAS/Flash drives – 2 U 15 x 3.5" SAS/Flash drives – 3 U	25 x 2.5" SAS/Flash drives – 2 U 15 x 3.5" SAS/Flash drives – 3 U
Standby Power System	1U 1.2KW	1U 1.2KW	1U 1.2KW	1U 1.2KW	1U 1.2KW
Raid Options	0/1/10/3/5/6	0/1/10/3/5/6	0/1/10/3/5/6	0/1/10/3/5/6	0/1/10/3/5/6
CPU/Memory per Array	Intel Xeon 5600/8 GB	Intel Xeon 5600/16 GB	Intel Xeon 5600/24 GB	Intel Xeon 5600/36 GB	Intel Xeon 5600/48 GB
Max Block Flex IO Modules per Array	0	4	4	10	10
Embedded IO Ports per Array	8 FC ports and 2 BE SAS buses	8 FC ports and 2 BE SAS buses	8 FC ports and 2 BE SAS buses	0	0
Max Total Ports per Array	8	24	24	24	32
2/4/8 Gb/s FC Max Ports per Array	8	16	16	24	32
1 GBaseT iSCSI Max Total Ports per Array	N/A	8	16	16	16
10 GbE iSCSI Min/Max Total Ports per Array	N/A	4	8	12	12
Max FCoE Total Ports per Array	N/A	4	8	12	16
6 Gb/s SAS Buses for DAE Connections	2	2	2	4	4 or 8
FILE COMPONENTS*					
# File X-Blades	N/A	1-2	1-3	2-4	2-8
# Control Stations	N/A	1-2 x 1U Server	1-2 x 1U Server	1-2 x 1U Server	1-2 x 1U Server
X-Blade: CPU/Memory	N/A	Intel Xeon 5600/6 GB	Intel Xeon 5600/12 GB	Intel Xeon 5600/12 GB	Intel Xeon 5600/24 GB
Max File Flex IO Modules per X-Blade	N/A	3	4	4	5
Min/Max 2/4/8 Gb/s FC Ports per X-Blade	N/A	4	4	4	4
Max IP Ports per X-Blade	N/A	8	12	12	16
Max 1 GBaseT Ports per X-Blade	N/A	8	12	12	16
Max 10 GbE Ports per X-Blade	N/A	4	6	6	8
OTHER					
Management	LAN 2 x 10/100/1000 Copper GbE	LAN 2 x 10/100/1000 Copper GbE	LAN 2 x 10/100/1000 Copper GbE	LAN 2 x 10/100/1000 Copper GbE	LAN 2 x 10/100/1000 Copper GbE
FUNCTIONAL LIMITS					
Max Raw Capacity	150 TB	240 TB	480 TB	984 TB	1,974 TB
Max SAN Hosts	512	2,048	4,096	4,096	8,192
Max Number of Pools	10	20	40	40	60
Max Number of LUNs	512	2,048	4,096	4,096	8,192
Max LUN Size	2 TB	2 TB	2 TB	2 TB	2 TB
Max File System Size	N/A	16 TB	16 TB	16 TB	16 TB
Maximum Usable File Capacity per X-Blade	N/A	200 TB	256 TB	256 TB	256 TB
OS Support	Block OS's see EMC E-Lab™ Navigator on EMC Powerlink™	Block OS's Plus File OS's see E-Lab Navigator and NAS Support Matrix on Powerlink	Block OS's Plus File OS's see E-Lab Navigator and NAS Support Matrix on Powerlink	Block OS's Plus File OS's see E-Lab Navigator and NAS Support Matrix on Powerlink	Block OS's Plus File OS's see E-Lab Navigator and NAS Support Matrix on Powerlink

* The File components are not required when ordering a block-only system.

VNX CONNECTIVITY

The VNX series provides flexible connectivity options via Flex IO modules for both the file X-blades for NAS connectivity and the block storage processors for FC and iSCSI host connectivity (see above table for number of modules supported per blade or SP).

BLOCK-TO-HOST CPU (SP-BASED) FLEX IO MODULE OPTIONS

IO Module	Description
Four-Port Fibre Channel Module	FC module with four ports auto-negotiating to 2/4/8 Gbps; uses optical SFP and OM2/OM3 cabling to connect directly to host HBA or FC switch
Four-Port 1 Gb/s iSCSI Module with TOE	iSCSI module with four 1 GBaseT RJ-45 copper connections to Cat 6 cabling to Ethernet switch; includes TCP offload engine
Two-Port 10 Gb/s iSCSI Module with TOE	iSCSI module with two 10 Gb/s Ethernet ports and choice of SFP+ optical connection or active twinax copper connection to Ethernet switch; includes TCP offload engine
Two-Port 10 GbE FCoE Module	FCoE module with two 10 Gb/s Ethernet ports and choice of SFP+ optical connection or active twinax copper connection to converged enhanced Ethernet switch

FILE-TO-NFS/CIFS CLIENT (X-BLADE-BASED) FLEX IO MODULE OPTIONS

IO Module	Description
Four-Port 1 GBase-T IP Module	10/100/1000 BaseT module with four ports supporting RJ-45 copper connections to Cat 6 cabling to Ethernet switch
Four-Port 1 GBaseT and 1 GbE Opt IP Module	IP module with two ports of 10/100/1000 Base-T and two ports 1 GbE optical
Two-Port 10 GbE Opt IP Module	IP module with two 10 Gb/s Ethernet ports and choice of SFP+ optical connection or active twinax copper connection to Ethernet switch
Four-Port 8 Gb/s Fibre Channel Module	FC module with four ports auto-negotiating to 2/4/8 Gbps; uses optical SFP and OM2/OM3 cabling to connect directly to captive array and to provide NDMP tape connection

MAXIMUM CABLE LENGTHS

Shortwave optical OM2: 50 meters (8 Gb), 100 meters (4 Gb), and 300 meters (2 Gb)

Shortwave optical OM3: 150 meters (8 Gb), 380 meters (4 Gb), and 500 meters (2 Gb)

BACK-END (DISK) CONNECTIVITY

Each storage processor connects to one side of each of two or four (or optionally eight for the VNX7500) redundant pairs of four-lane x 6 Gb/s Serial Attached SCSI (SAS) buses, providing continuous drive access to hosts in the event of a storage processor or bus fault. VNX models require a minimum of four “vault” drives (SAS) and support a maximum of 1000 disk drives in up to 67 disk expansion chassis. Approximately 200 GB per vault drive is consumed by VNX operating environment software and data structures.

SUPPORTED DISK EXPANSION CHASSIS (DAES)

	15x3.5” Drive DAE	25x2.5” Drive DAE
Drive Types Supported	3.5” Flash 3.5” 15K Rotating 2.5” 10K Rotating 3.5” Near-line Rotating	2.5” 10K Rotating
Drive Mixing	No limitations	No limitations
Controller Interface	6 Gb SAS	6 Gb SAS

DISK DRIVES FOR 15 X 3.5" DRIVE DISK PROCESSOR ENCLOSURE/DISK ARRAY ENCLOSURE

Nominal Capacity	100 GB Solid State Drive	200 GB Solid State Drive	300 GB 15K Drive	600 GB 15K Drive	300 GB 10K Drive	600 GB 10K Drive	2 TB 7.2K Drive*
Formatted Capacity*	93.1 GB	186.31 GB	272.59 GB	545.19 GB	272.59 GB	545.19 GB	1,852.09 GB
Drive Form Factor	3.5"	3.5"	3.5"	3.5"	2.5"	2.5"	3.5"
Height	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"
Rotational Speed	Solid State	Solid State	15,000 rpm	15,000 rpm	10,000 rpm	10,000 rpm	7,200 rpm
Interface	6 Gb SAS	6 Gb SAS	6 Gb SAS	6 Gb SAS	6 Gb SAS	6 Gb SAS	6 Gb SAS
Data Buffer	N/A SSD	N/A SSD	16 MB min	16 MB min	16 MB min	16 MB min	16 MB min
ACCESS TIME							
Average Read	N/A	N/A	3.4 msec	3.4 msec	3.6 msec	3.7 msec	8.5 msec
Average Write	N/A	N/A	3.9 msec	3.9 msec	4.2 msec	4.2 msec	9.5 msec
Rotation Latency	N/A	N/A	2.0 msec	2.0 msec	3.0 msec	3.0 msec	4.16 msec
NOMINAL POWER CONSUMPTION (WATTS)							
Operating Mode	4.97	4.97	12.92	16.35	6.15	5.6	12.2
Idle Mode	1.36	1.36	8.74	11.68	3.5	3.1	8.0

DISK DRIVES FOR 25 X 2.5" DRIVE DISK PROCESSOR ENCLOSURE/DISK ARRAY ENCLOSURE

Nominal Capacity	300 GB 10K Drive	600 GB 10K Drive
Formatted Capacity*	272.59 GB	545.19 GB
Form Factor	2.5"	2.5"
Height	1.0"	1.0"
Rotational Speed	15,000 rpm	10,000 rpm
Interface	6 Gb SAS	6 Gb SAS
Data Buffer	16 MB min	16 MB min
ACCESS TIME		
Average Read	3.6 msec	3.7 msec
Average Write	4.2 msec	4.2 msec
Rotation Latency	3.0 msec	3.0 msec
NOMINAL POWER CONSUMPTION (WATTS)		
Operating Mode	6.15	5.6
Idle Mode	3.5	3.1

* 520 bytes/sector, 1 MB = 1,048,576 bytes

VNX OE PROTOCOLS AND SOFTWARE FACILITIES

The VNX series offers support for a wide variety of protocol and advanced features available via various software suites and packs.

PROTOCOLS AND FACILITIES SUPPORTED

- Access-based Enumeration (ABE) for Microsoft Windows® Server 2003
- Address Resolution Protocol (ARP)
- Automated Volume Management (AVM): File system provisioning
- Block Protocols: iSCSI, Fibre Channel (FCP SCSI-3), and FCoE
- DFS Distributed File System (Microsoft) as Leaf node or Root Server
- Ethernet Trunking
- File Protocols: NFSv2, v3, and v4; CIFS (SMB 1 and SMB 2); FTP (including SFTP and FTPs)
- FileMover API: Open API for automated, transparent data movement between tiers of storage Network Lock Manager (NLM) v1, v3, and v4
- Failsafe Networking
- Internet Control Message Protocol (ICMP)
- Kerberos Authentication
- Lightweight Directory Access Protocol (LDAP)
- LDAP signing for Windows
- Link Aggregation (IEEE 802.3ad)
- UNIX archive utilities (tar/cpio)
- Network Data Management Protocol (NDMP) v1-v4
- Network Information Service (NIS) Client
- Network Status Monitor (NSM) v1
- Object support via EMC Atmos™ Virtual Edition
- Portmapper v2
- Network Time Protocol (NTP) client
- NT LAN Manager (NTLM)
- Routing Information Protocol (RIP) v1-v2
- Simple Network Management Protocol V1-V3 (SNMP)
- Simple Network Time Protocol (SNTP)
- Virtual Data Movers for Microsoft Windows clients
- Virtual LAN (IEEE 802.1q)

VNX SOFTWARE

	VNX5100	VNX5300, VNX5500, VNX5700, and VNX7500
Management	Unisphere™ for Block	Unisphere for Block, Unisphere for File, or Unisphere for Unified
Protocols	FC included	CIFS, NFS, pNFS, MPFS, FC, FCoE, iSCSI included
Base Software (included with VNX OE)	EMC Virtual Provisioning™	File Single Instancing Compression Virtual Provisioning

SOFTWARE SUITES

FAST Suite: Automatically optimize for the highest system performance and the lowest storage cost simultaneously	Extendable cache for performance boost Trend analysis and reporting Monitor and achieve performance objectives	Dynamically tier data across drives Extendable cache for performance boost Trend analysis and reporting Monitor and achieve performance objectives
Security and Compliance Suite: Keep data safe from changes, deletions, and malicious activity	Encrypt data where it is created	Encrypt data where it is created Disk-based WORM functionality Anti-virus integration and alerting

Local Protection Suite: Practice Safe Data Protection and Repurposing	Block storage snaps and clones Continuous Data Protection for DVR-like recovery for block storage	Block storage snaps and clones Continuous Data Protection for DVR-like recovery for block storage File system snaps
Remote Protection Suite: Protect data against localized failures, outages, and disasters	Unified storage replication with DVR-like recovery Integrated WAN deduplication and bandwidth reduction	Unified storage replication with DVR-like recovery Integrated WAN deduplication and bandwidth reduction Granular file system level replication and recovery
Application Protection Suite: Automate application copies and prove compliance	Application copy management Prove protection compliance	Application copy management Prove protection compliance
SOFTWARE PACKS		
Protection Pack	Local Protection Suite + Remote Protection Suite + Application Protection Suite	Local Protection Suite + Remote Protection Suite + Application Protection Suite
Total Value Pack	Security & Compliance Suite + Local Protection Suite + Remote Protection Suite + Application Protection Suite	NA
Total Efficiency Pack	NA	FAST Suite + Security & Compliance Suite + Local Protection Suite + Remote Protection Suite + Application Protection Suite

NOTE: For more detail on software licensing, please contact your sales representative.

OPTIONAL VMware FACILITIES AND TITLES

- VNX Plug-in for VMware®: For provisioning, management, cloning, and deduplication
- Site Recovery Manager (SRM) Integration: Managing failover and failback making disaster recovery rapid and reliable
- Replication Manager: Host-based management of array-based copies of data

ADDITIONAL OPTIONAL EMC TITLES

- EMC Ionix™: VNX integration with EMC Storage management infrastructure
- EMC PowerPath®: Path management
- EMC File Management Appliance (FMA and FMA/VE): Policy based file archiving

VNX ELECTRICAL SPECIFICATIONS

(For specific power specifications please refer to the EMC Power Calculator at power.emc.com with your Powerlink account.)

DPE AND SPE ENCLOSURES

	VNX5100 DPE (15x3.5" drives)	VNX5100 DPE (25x2.5" drives)	VNX5300 DPE (15x3.5" drives)	VNX5300 DPE (25x2.5" drives)	VNX5500 DPE (15x3.5" drives)	VNX5500 DPE (25x2.5" drives)	VNX5700 SPE	VNX7500 SPE	
POWER									
AC Line Voltage	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	
AC Line Current (operating maximum)	4.2 A max at 100 Vac, 2.1 A max at 200 Vac	4.0 A max at 100 Vac, 2.0 A max at 200 Vac	4.8 A max at 100 Vac, 2.4 A max at 200 Vac	4.6 A max at 100 Vac, 2.3 A max at 200 Vac	4.8 A max at 100 Vac, 2.4 A max at 200 Vac	4.6 A max at 100 Vac, 2.3 A max at 200 Vac	5.3 A max at 100 Vac, 2.7 A max at 200 Vac	5.3 A max at 100 Vac, 2.7 A max at 200 Vac	
Power Consumption (operating maximum)	415 VA (390 W) max	395 VA (385 W) max	480 VA (455 W) max	460 VA (450 W) max	480 VA (455 W) max	460 VA (450 W) max	530 VA (500 W) max	530 VA (500 W) max	
Power Factor	0.98 min at full load, low voltage	0.98 min at full load, low voltage	0.98 min at full load, low voltage	0.98 min at full load, low voltage	0.98 min at full load, low voltage	0.98 min at full load, low voltage	0.98 min at full load, low voltage	0.98 min at full load, low voltage	
Heat Dissipation (operating maximum)	1.40 x 10 ⁶ J/hr, (1,330 Btu/hr) max	1.39 x 10 ⁶ J/hr, (1,320 Btu/hr) max	1.64 x 10 ⁶ J/hr, (1,560 Btu/hr) max	1.62 x 10 ⁶ J/hr, (1,540 Btu/hr) max	1.64 x 10 ⁶ J/hr, (1,560 Btu/hr) max	1.62 x 10 ⁶ J/hr, (1,540 Btu/hr) max	1.80 x 10 ⁶ J/hr, (1,710 Btu/hr) max	1.80 x 10 ⁶ J/hr, (1,710 Btu/hr) max	
In-rush Current	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	
Startup Surge Current	29 A rms max for 50 ms, at any line voltage	29 A rms max for 50 ms, at any line voltage	29 A rms max for 50 ms, at any line voltage	29 A rms max for 50 ms, at any line voltage	29 A rms max for 50 ms, at any line voltage	29 A rms max for 50 ms, at any line voltage	27 A rms max for 50 ms, at any line voltage	27 A rms max for 50 ms, at any line voltage	
AC Protection	12.5 A fuse on each power supply, both phases	12.5 A fuse on each power supply, both phases	12.5 A fuse on each power supply, both phases	12.5 A fuse on each power supply, both phases	12.5 A fuse on each power supply, both phases	12.5 A fuse on each power supply, both phases	7.8 A fuse on each power supply, both phases	7.8 A fuse on each power supply, both phases	
AC Inlet Type	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	
Ride-through Time	30 ms min	30 ms min	30 ms min	30 ms min	30 ms min	30 ms min	30 ms min	30 ms min	
Current Sharing	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	
DIMENSIONS									
Height (in./cm)	5.25 in./ 13.34 cm	5.25 in./ 13.34 cm	5.25 in./ 13.34 cm	5.25 in./ 13.34 cm	5.25 in./ 13.34 cm	5.25 in./ 13.34 cm	3.5 in./ 8.9 cm	3.5 in./ 8.9 cm	
Width (in./cm)	17.5 in./ 44.45 cm	17.5 in./ 44.45 cm	17.5 in./ 44.45 cm	17.5 in./ 44.45 cm	17.5 in./ 44.45 cm	17.5 in./ 44.45 cm	17.5 in./ 44.5 cm	17.5 in./ 44.5 cm	
Depth (in./cm)	24.25 in./ 61.6 cm	24.25 in./ 61.6 cm	24.25 in./ 61.6 cm	24.25 in./ 61.6 cm	24.25 in./ 61.6 cm	24.25 in./ 61.6 cm	24.25 in./ 61.6 cm	24.25 in./ 61.6 cm	
Weight (lb/kg) (with and without drives)	Full: 96.4/43.8 Empty: 62.4/28.36	Full: 73.4/33.36 Empty: 59.9/27.2	Full: 96.4/43.8 Empty: 62.4/28.36	Full: 73.4/33.36 Empty: 59.9/27.2	Full: 96.4/43.8 Empty: 62.4/28.36	Full: 73.4/33.36 Empty: 59.9/27.2	Full: 73.4/33.36 Empty: 59.9/27.2	52.5 lb/23.81 kg	52.5 lb/23.81 kg

NOTE: Each DPE or SPE requires a Standby Power Supply (see the following information)

STANDBY POWER SUPPLY

POWER	1.2kW Standby Power Supply
AC Line Voltage	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz
AC Line Current, Internal and Pass-through	0.10 A max at 100 Vac, internal power consumption (Up to 10 A max at 100 Vac, pass-through to AC outlets) 0.05 A max at 200 Vac, internal power consumption (Up to 6 A max at 200 Vac, pass-through to AC outlets)
Internal Power Consumption	70 VA (40 W) pk in hi-charge mode, 10 VA (6 W) in float charge mode
Power Factor	N/A for pass-through load, internal 10 VA load is 0.60 power factor
Heat Dissipation	21.6 x 103 J/hr, (20 Btu/hr) steady state
In-rush Current	9 A max for ½ line cycle, per power supply at 240 Vac
AC Protection	15 A fuse, both phases
AC Inlet Type	IEC320-C14 appliance coupler with switch
AC Outlet Type	IEC320-C13 appliance coupler, quantity two
Charge Times	190 minutes max
AC Failure Detect Time	10 ms max
Transfer Time	25 ms max
Dimensions (H/W/L)	1.6 in/17.5 in/23.75 in or 4.0 cm/44.45 cm/60.3 cm
Weight	47 lb/21.6 Kg

DATA MOVER ENCLOSURES, DISK ARRAY ENCLOSURES AND CONTROL STATION

	VNX5300 DME with (2) Data Movers	VNX5500 DME with (2) Data Movers	VNX5700 DME with (2) Data Movers	VNX7500 DME with (2) Data Movers	15x3.5" Disk Array Enclosure	25x2.5" Disk Array Enclosure	Control Station
POWER							
AC Line Voltage	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz	100 to 240 Vac ± 10%, single-phase, 47 to 63 Hz
AC Line Current (operating maximum)	4.7 A max at 100 Vac, 2.3 A max at 200 Vac	5.0 A max at 100 Vac, 2.5 A max at 200 Vac	5.3 A max at 100 Vac, 2.7 A max at 200 Vac	5.3 A max at 100 Vac, 2.7 A max at 200 Vac	2.8 A max at 100 Vac, 1.4 A max at 200 Vac	2.5 A max at 100 Vac, 1.3 A max at 200 Vac	1.0 A max at 100 Vac, 0.5 A max at 200 Vac
Power Consumption (operating maximum)	465 VA (440 W) max	500 VA (470 W) max	530 VA (500 W) max	530 VA (500 W) max	280 VA (235 W) max	250 VA (230 W) max	132 VA (104 W) max
Power Factor	0.98 minimum at full load, low voltage	0.98 minimum at full load, low voltage	0.98 minimum at full load, low voltage	0.98 minimum at full load, low voltage	0.98 min at full load, low voltage	0.98 min at full load, low voltage	0.80 min at full load, low voltage
Heat Dissipation (operating maximum)	1.58 x 106 J/hr, (1,500 Btu/hr) max	1.69 x 106 J/hr, (1,610 Btu/hr) max	1.80 x 106 J/hr, (1,710 Btu/hr) max	1.80 x 106 J/hr, (1,710 Btu/hr) max	8.46 x 105 J/hr, (800 Btu/hr) max	8.28 x 105 J/hr, (785 Btu/hr) max	3.60 x 105 J/hr, (300 Btu/hr) max
In-rush Current	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle, per line cord at 240 Vac 8 A max for ½ line cycle, per line cord at 120 Vac	50 A max for ½ line cycle, per line cord at 240 Vac 25 A max for ½ line cycle, per line cord at 120 Vac	50 A max for ½ line cycle, per line cord at 240 Vac 25 A max for ½ line cycle, per line cord at 120 Vac	15 A max for ½ line cycle at 240 Vac 8 A max for ½ line cycle at 120 Vac
Startup Surge Current	27 A rms max for 50 ms, at any line voltage	27 A rms max for 50 ms, at any line voltage	27 A rms max for 50 ms, at any line voltage	27 A rms max for 50 ms, at any line voltage	10.6 A rms max for 100 ms, at any line voltage	10.6 A rms max for 100 ms, at any line voltage	NA
AC Protection	7.8 A fuse on each power supply, both phases	7.8 A fuse on each power supply, both phases	7.8 A fuse on each power supply, both phases	7.8 A fuse on each power supply, both phases	10 A fuse on each power supply, both phases	10 A fuse on each power supply, both phases	NA
AC Inlet Type	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone	IEC320-C14 appliance coupler, per power zone
Ride-through Time	30 ms min	30 ms min	30 ms min	30 ms min	30 ms min	30 ms min	NA
Current Sharing	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 15 percent of full load, between power supplies	± 10 percent of full load, between power supplies	± 10 percent of full load, between power supplies	NA

	VNX5300 DME with (2) Data Movers	VNX5500 DME with (2) Data Movers	VNX5700 DME with (2) Data Movers	VNX7500 DME with (2) Data Movers	15x3.5" Disk Array Enclosure	25x2.5" Disk Array Enclosure	Control Station
DIMENSIONS							
Height (in./cm)	3.5 in/8.9 cm	3.5 in/8.9 cm	3.5 in/8.9 cm	3.5 in/8.9 cm	5.25 in/13.34 cm	3.45 in/8.76 cm	1.75 in/4.45 cm
Width (in./cm)	17.5 in/44.45 cm	17.5 in/44.45 cm	17.5 in/44.45 cm	17.5 in/44.45 cm	17.6 in/44.75 cm	17.62 in/44.75 cm	17.5 in/44.45 cm
Depth (in./cm)	24.25 in/61.6 cm	24.25 in/61.6 cm	24.25 in/61.6 cm	24.25 in/61.6 cm	14 in/35.56 cm	13 in/33.02 cm	20 in/50.8 cm
Weight (lb/kg) (with and without drives)	52.5 lb/23.81 kg	52.5 lb/23.81 kg	52.5 lb/23.81 kg	52.5 lb/23.81 kg	Full: 68/30.9 Empty: 32/14.5	Full: 45/20.45 Empty: 35/15.9	18 lb/8.16 kg

¹Ratings assume a fully loaded DAE that includes two power supplies, two LCCs, and 15 disk drives.

²Ratings assume a fully loaded DAE that includes two power supplies, two LCCs, and 25 disk drives.

40U CABINET

AC Voltage:	200 to 240 Vac ± 10 percent, single-phase, 47 to 63 Hz
Power Configuration:	Two power domains (base and extended), each redundant
Power Inlet Count:	Either two (for redundant base configuration) or four (for redundant extended configuration)
Plug Types:	NEMA L6-30P or IEC309-332 P6 or IP57 (Australia)
Input Power Capacity:	4,800 VA @ 200 VAC, 5,760 VA @ 240 VAC (base configuration) 9,600 VA @ 200 VAC, 11,520 VA @ 240 VAC (extended configuration)
AC Protection:	30 A site circuit breakers on each power branch

OPERATING ENVIRONMENT

Temperature:	50–104 degrees F (10–40 degrees C)
Temperature Gradient:	18 degrees F/hr (10 degrees C/hr)
Relative Humidity:	20% to 80% (non-condensing)
Altitude:	7,500 ft. (2,286.4 m) @ 104 degrees F (40 degrees C) max. 10,000 ft (3,048 m) @ 98.6 degrees F (37 degrees C) max.

ELECTROMAGNETIC EMISSIONS AND IMMUNITY

FCC Class A EN55022 Class A

CE Mark VCCI Class A (for Japan)

ICES-003 Class A (for Canada) AS/NZS 3548 Class A (for Australia/New Zealand)

EN55024 Immunity, ITE BSMI Class A (for Taiwan)

QUALITY AND SAFETY STANDARDS

UL 60950; CSAC 22.2-60950, FN 60950

Manufactured under an ISO 9000-registered quality system

ETSI EN 300 386

CONTACT US

To learn more about how EMC products, services, and solutions can help solve your business and IT challenges, contact your local representative or authorized reseller, or visit us at www.EMC.com.

EMC², EMC, EMC Virtual Positioning, Atmos, E-Lab, Ionix, PowerPath, Powerlink, Unisphere, VNX, VNX5100, VNX5300, VNX5500, VNX5700, VNX7500, the EMC logo, and where information lives are registered trademarks or trademarks of EMC Corporation in the United States and other countries. VMware and the VMware logo are registered trademarks or trademarks of VMware, Inc., in the United States and other jurisdictions. Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and other countries. All other trademarks used herein are the property of their respective owners.
© Copyright 2010 EMC Corporation. All rights reserved. Published in the USA. 12/10 Specification Sheet H8514