

B60™

Specification Sheet

Specifications	
Disk Bays	60
Rack U	4U
Controllers	1 Standard
	Dual Optional
	Dual RAID Engines per Controller
Supports B60E	NO
Supports SATA and SAS Disks	YES
Battery Protected Cache per Controller	4GB Standard
Host Ports	2 FC 8Gbit and 2 iSCSI 1Gbit Ports
	per Controller
Hardware RAID 6	Included
RAID Levels	0, 1, 1+0, 4, 5, 6
Volumes and LUNs	254 volumes per system / 254 LUNs per port
Standard Dual Redundant Power Supplies	2 Redundant Standard 1600 watt – 220-240v Only
Dimensions	Width, with flanges is 19 inches / 48.26 cm. Fits into a standard 19 inch rack (16.9 inches / 43.00 cm chassis width)
	Height is 7 inches / 17.78 cm. (4U)
	Depth is 40.36 inches / 102.6 cm. (does not require cable mgt. unit is fixed)
Maximum Installed Weight w/ mounting rails, all drives and controllers	approx - 102 Kg / 225 lbs
Operating Temperature Range	5°C to 35°C (41°F to 95°F)
Operating Humidity Range	20% to 80% non-condensing
Operating Altitude	0 to 2,133m (0 to 7,000ft)
Non-operational Altitude	0 to 12,192m (0 to 40,000ft)



B60™

Specifications Cont.	
Global "Hot Disk Spares"	Yes
Hot-pluggable Controllers, Expansion Modules, Disks, Power Supplies	Yes
Multiple RAID sets and LUNs per RAID set	Yes
254 volumes per system / 254 LUNs per port	Yes
ACL with read only, read and write and denied access policies	Yes
Nexsan multi-unit manager software	Yes
Onboard Browser Based GUI	Yes
Nexsan Tele-Guard Phone Home Manager	Yes
3 yr. Warranty, Advanced Exchange, 24 x 7 Support	Yes

Note: a 1200mm rack is recommended for mounting the B60



AUTHORIZED RESELLER

60TM



Inside US: 888.472.8028 | Local: 928.284.2535 | Fax: 928.441.8126 | Email: sales@condorstorage.com